



## PRODUCT FEATURES

### ULTRAGEAR EP 80W-90 GL-5

ULTRAGEAR EP 80W-90 paraffinic base oils, produced by the addition of a special multi-grade gear oil additive package. Especially developed for hypoid type gear boxes, multigrade gear oil suitable for use in all four seasons

#### Applications

Exposed to extreme pressure, high speed and cars, heavy duty trucks and construction machinery gearboxes and differentials with hypoid, bevel and helical gear systems. High-performance heavy-duty automotive gear oil.

#### Technical Specifications

- Heavy and impact loads, vibration shows the high performance working conditions,
- High operating temperatures provides superior protection against wear and tear,
- Multigrade properties and can be used safely in all four seasons,
- fluidity at low temperatures, preserving the life of the equipment, especially the first studies extend,
- Corrosion and rust preventive additives protects the surface of the gear,
- extending oil change periods, reduces maintenance costs.

#### performance

API GL-5

#### Typical Properties

Density 15 °C g/mL	0.904
Viscosity 40 °C, mm <sup>2</sup> /s	198
Viscosity 100 °C mm <sup>2</sup> /s	18
Viscosity Index	98
Flash Point° C	210
Pour Point, ° C	-24

#### PACKAGING

4L	PLASTIC
15kg	TIN
180 kg	DRUM

#### Warnings and Suggestions

Waste oil, soil, water, sewer, and trash pour. Clean, solid and tightly sealed in a container delivered to the nearest waste oil collection center please. Keep away from children, avoid continuous and long-term contacts. If swallowed, do not induce vomiting by force, seek medical attention. Do not leave exposed to direct sunlight. Store in a closed area, Keep it away from damp and humid environments.