



PRODUCT FEATURES

NATURAL GREASE

NATURAL composed of grease-quality base oils and calcium soap, general-purpose suitable for use in grease.

Applications

Operating temperatures do not exceed 80 oC applied heavy loads at low speed rotating lubrication of bearings, chassis and other miscellaneous components used in gresajinda. general

It is recommended for industrial use.

Technical Specifications

- Contains special additives to prevent corrosion. Provides superior protection against rust,
- ease of use in different ranges of penetration,
- Easy to pump,
- resistance to water washout,
- Heavy work is sought out criteria for the systems are preferred due to economical,
- Other greases are painted green to decouple special.

Typical Properties

NLGI Numarası		0	1	2	3
Color		Brown	Brown	Brown	Brown
Soap Type		Calcium	Calcium	Calcium	Calcium
Penetration	25 °C/60 Stroke	355/385	310/340	265/295	220/250
Dropping Point ° C	°C	100	100	100	100
Base Oil		Mineral	Mineral	Mineral	Mineral
Base Oil Viscosity	40°C cSt	220	220	220	220
Base Oil Viscosity	100°C cSt	18,30	18,30	18,30	18,30
Operating Temperature	Max °C	-10/+60	-10/+60	-10/+60	-10/+60

PACKAGING

1 kg	TIN BOX
4 kg	TIN BOX
16 kg	PAIL
50 kg	MINI BARREL
180 kg	DRUMS

Warnings and Suggestions

Waste oil, soil, water, sewer, and trash pour. Clean, solid and tightly sealed in a container delivered to the nearest waste oil collection center please. Keep away from children, avoid continuous and long-term contacts. If swallowed, do not induce vomiting by force, seek medical attention. Do not leave exposed to direct sunlight. Store in a closed area, Keep it away from damp and humid environments.